

Dealer:



03/2019-50023372 | www.Weirich-PR.de 0



Pre-Pruner

VSL 07 P & VS 98 S



Details and illustrations should be considered to be approximate. The products illustrated sometimes include special equipment which is not part of the standard version. We reserve the right to make technical and design changes.

ERO GmbH | Am ERO-Werk | 55469 Simmern | Germany
Tel.: +49 6761-9440-0 | Fax: +49 6761-9440-1099 | mail@ero.eu
www.Binger-Seilzug.de

Fotos: www.Petra-Stauning.de, www.ruetkes-fotodesign.de



More than 20 years experience with Pre-Pruners mean unbeatable value for you: Binger offers you two different Pre-Pruner models, VSL 07 P and VS 98 S, and numerous options – the right choice for every application.



Binger Pre-Pruner VSL 07 P

The VSL 07 P is the lightest model in the Binger range of Pre-Pruners. Counter-rotating shearing discs cut the vines at the desired height. The exposed shearing discs allow vines to be cut back even before the leaves have fallen without the risk of leaves blocking the pruner.

There is a separate hydraulic motor for each of the cylinders that carry the shearing discs. When driving into a row, or on reaching a post, pressing a button opens the cylinders.

Three frame sizes permit nine different cutting lengths between 21 and 105 centimetres. This ensures optimum adaptation of the machine to an existing vineyard.



Adjusting to a different cutting length takes very little time. The VSL07 P is therefore just as suitable for cordon-trained as for cane-pruned vines. Its low weight makes the VSL07 P suitable also for use on steep slopes and in difficult terrain.

Standard equipment:

- Frame with cutting elements
- Hydraulic controls
- Trigger to open the unit manually at a post (opens the cutting elements about 30 cm)
- Guards and protective equipment

Options:

- Machine equipped with saws (e.g. for cordon-trained vines)
- Automatique Opening AOS
- Storage frame VSL 07



Operator panel AOS

Binger Pre-Pruner VS 98 S

Model VS 98 S is ideally suited for use where there is very vigorous canopy growth. To protect the wire trellis, the saw blades are surrounded by a screen and arranged on one side only. The offset pressure discs guide vine canes continually to the saw blades. The hydraulic drive for the saw blades can cope with substantial cane thicknesses. A clean cut is guaranteed even with dense foliage.



Standard equipment:

- Speed of screens adjustable from driver's seat
- Trigger to open the unit manually at a post

Options:

- Automatique Opening AOS
- Storage Frame VS 98

The speed of rotation of the pressure discs and screen is adjustable so that pruning can be adapted to the running speed.

The VS 98 S is available in a range of cutting lengths from 18 cm to 81 cm, and with 9 or 12 cm saw spacing. Optionally, a larger frame can be supplied with 20 centimetres additional clearance above the saws.